

**Amendment to the Claims:**

The listing of claims will replace all prior versions, and listings of claims in the application:

**Listing of Claims:**

1-26. Cancelled.

27. (Currently Amended) A method for constructing a reservoir model representative of an underground reservoir, including discretizing said reservoir by a set of grid cells, and associating with said reservoir model a permeability field constrained by a priori geologic data and dynamic data collected in said reservoir by measurements and observations comprising:

a) constructing an initial reservoir model including generating a permeability field in accordance with a stochastic model, coherent with the a priori geologic data;

b) identifying zones inside said reservoir;

c) calculating effective permeabilities of said zones and carrying out, by means of a simulator, a simulation of fluid flows, to estimate corrections to be brought to said effective permeabilities to improve calibration in relation to said dynamic data; and

d) propagating said corrections to said set of grid cells of said reservoir model, by means of an iterative optimization process comprising minimizing a function which depends on said corrections, using a technique of gradual deformation of realizations of said stochastic model.

28. (Currently Amended) A method as claimed in claim 27, wherein ~~said zones are defined either manually or automatically from said flow simulator~~ the method is for developing of oil reservoirs by constructing the reservoir model and using the reservoir model to develop the underground reservoir.

29. (Currently Amended) A method as claimed in claim ~~27~~28, wherein flow simulation is carried out by means of a streamline simulator, ~~and said zones of said underground reservoir are identified by a set of grid cells traversed by one or more streamlines of fixed geometry~~ and said zones are defined either manually or automatically from said flow simulator.

30. (Previously Presented) A method as claimed in claim 28, wherein flow simulation is carried out by means of a streamline simulator and said zones of said underground reservoir are identified by a set of grid cells traversed by one or more streamlines of fixed geometry.

31. (Currently Amended) A method as claimed in claim ~~27~~28, wherein said zones are identified as volume portions on a periphery of wells running through said reservoir, within a framework of well tests.

32. (Previously Presented) A method as claimed in claim 28, wherein said zones are identified as volume portions on a periphery of wells running through said reservoir, within a framework of well tests.

33. (Previously Presented) A method as claimed in claim 29, wherein said zones are identified as volume portions on a periphery of wells running through said reservoir, within a framework of well tests.

34. (Previously Presented) A method as claimed in claim 30, wherein said zones are identified as volume portions on a periphery of wells running through said reservoir, within a framework of well tests.

35. (Currently Amended) A method as claimed in claim ~~27~~28, wherein at least one gradual deformation parameter is assigned to each of said zones.

36. (Previously Presented) A method as claimed in claim 28, wherein at least one gradual deformation parameter is assigned to each of said zones.

37. (Previously Presented) A method as claimed in claim 29, wherein at least one gradual deformation parameter is assigned to each of said zones.

38. (Previously Presented) A method as claimed in claim 30, wherein at least one gradual deformation parameter is assigned to each of said zones.

39. (Previously Presented) A method as claimed in claim 31, wherein at least one gradual deformation parameter is assigned to each of said zones.

40. (Previously Presented) A method as claimed in claim 32, wherein at least one gradual deformation parameter is assigned to each of said zones.

41. (Previously Presented) A method as claimed in claim 33, wherein at least one gradual deformation parameter is assigned to each of said zones.

42. (Previously Presented) A method as claimed in claim 34, wherein at least one gradual deformation parameter is assigned to each of said zones.